

EK Ecoline Product Specialty




EK Ecoline Hoarding System

Construction Hoarding Guidelines

The hoarding should not be less than 1800mm in height and continuous down to the ground. It should be properly designed and constructed in accordance to the specification of the local authority and should be maintained in good condition.



Green Recycle



Construction Site Temporary Hoarding

Hoarding for construction sites Hoarding is a temporary structure of solid construction, erected around the perimeter of construction sites to shield them from view and prevent unauthorised access. It is an important component in ensuring health and safety, for site workers, visitors and the general public and can also be part of a site security system to prevent theft or vandalism.

EK Ecoline Temporary Hoarding & Permanent Fence

Have been widely used in the market. The prominent anti-corrosion performance of it, is suitable for the applications in coastal areas with serious salt fog corrosion and the areas with serious pollution, especially in chemical industries.



**EK Ecoline Permanent
Perimeter Fence
Elegance Outlook with
Cost Efficiency and
Effectiveness**

EK Ecoline Sliding Gate System " EKSG " (Light Weight & Heavy Duty)



Light
Weight &
Strong



What Are Sliding Gates?

EK Ecoline Sliding Gate System " EKSG " Are Using Slot In Concept Strong and Durability and Safe More Space Gate Storage with Huge Wide



☀ Sliding gates are similar to swing gates, in that they can open and close. However, a sliding gate moves in only one direction. It can slide back and forth if it is placed in a track

Benefits of Sliding Gates

Because they slide along the fence-line, this style of gate takes up minimal space. It also allows vehicles and pedestrians to access the property safely and easily. Sliding gates are ideal in situations where the access point is particularly wide.